





















<b>Produktdatenblatt</b> <i>Product data sheet</i>	<b>TEMO 6</b> Gitterrost <i>grating</i>	
---	---	--

	TEMO 6 ST	TEMO 6 V4A	TEMO 6 GFK
			
Gitterrost / grating			
Traverse / stringer, Profil / profile			
Stützenkopf / pedestal head			
Stützenfuß / pedestal base			
Verklebung / glueing			
<b><u>Gitterrostelement</u></b> <b><u>grating</u></b>			
Abmessung / dimensions		200...1200 x 200...1200	
Stärke / thickness	25 - 40mm	25 - 40mm	25 - 60mm
Ausführung	Pressrost	Schweißrost	monolithisch
Gewicht / weight	52 + kg/m <sup>2</sup>	54 + kg/m <sup>2</sup>	59 + kg /m <sup>2</sup>
Werkstoff / material	Stahl / steel	V4A 1.7145	GFK
<b><u>Beschichtungen</u></b> <b><u>coatings</u></b>			
ohne / bare	-	x	x
feuerverzinkt / hot dip galvanised	x	-	-
galvanisch verzinkt / galvanised	x	-	-
pulverbeschichtet / powder - coated	x	-	-
<b><u>Unterkonstruktion / pedestals, profiles</u></b>			
mögliche Anwendung / possibilities:	OKF in mm	OKF in mm	OKF in mm
M16 / M20	≥ 180 bis 2500	≥ 180 bis 2500	≥ 180 bis 2500
Stahl, galvanisch verzinkt / steel, galvanized	x	-	-
Stahl, feuerverzinkt / hot dip galv. steel	x	-	(x)
Stahl, pulverbeschichtet / powder - coated steel	x	-	(x)
Kunststoff , plastic (max h=1000mm)	(x)	(x)	x
Aluminium blank / aluminium	-	-	x
Alu, pulverbeschichtet / powder - coatet alum.	-	-	x
Edelstahl / stainless steel V4A 1.7145	-	x	x
	<b>TEMO 6 ST</b>	<b>TEMO 6 V4A</b>	<b>TEMO 6 GFK</b>
<b><u>Lastwerte / loading values</u></b>			
Punktlast / concentrate <i>Concentrated load</i> <small>(Belastungsfläche=200x200mm)</small>	1.000N-10.000N	1.000N-5.000N	1.000 N -4.000 N